

commBOX Interactive Classic Specs

Models					
SKU	Classic 55 CBIC55	Classic 65 CBIC65	Classic 75 CBIC75	Classic 86 CBIC86	Classic 98 CBIC98
Screen					
Resolution	UD 3840x2160 @60Hz			UD 3840x2160 @60Hz	
Brightness	450cd / m2			350cd / m2	
Viewing Angle	178°			178°	
Noise	Below 40dB 25C			Below 40dB 25C	
Surface Temp	Below 10 at 24C			Below 10 at 24C	
Operating Con	5C to 35C			5C to 35C	
Power Req	AC 100 to 240V, 50/60Hz Power Supply			AC 100 to 240V, 50/60Hz Power Supply	
Power Max	130W	260W	470W	470W	520W
Power Average	110W	240W	430W	430W	480W
Touch Points	4 / 10 Fingertips or any tips			4 /10 Fingertips or any tips	
Touch Technology	Optical			Optical	
LED Display	LG Commercial Grade			LG Commercial Grade	
VESA	456x400	456x400	400x600	400x606	400x744
Dimensions					
Screen	1413(W) x 838(H) x 102(D)mm	1638(W) x 960(H) x 108(D)mm	1840(W) x 1085(H) x 128(D)mm	2093(W) x 1234(H) x 125(D)mm	2368(W) x 1393(H) x 141(D)mm
Packed	1590(W) x 960(H) x 270(D)mm	1850(W) x 1100(H) x 320(D)mm	2050(W) x 1225(H) x 350(D)mm	2275(W) x 1360(H) x 400(D)mm	2600(W) x 1550(H) x 560(D)mm
Weight					
Screen	50kg	68kg	98kg	122kg	134kg
Packed	57kg	81kg	116kg	147kg	154kg
Accessories	HDMI Cable, USB Cable, Stylus Pen, Cleaning Cloth			HDMI Cable, USB Cable, Stylus Pen, Cleaning Cloth	
Speakers	15W x 2 Internal Speakers 15W x 2 Speaker Out 			15W x 2 Internal Speakers 15W x 2 Speaker Out 	
Input/Output	Input: VGA + 3.5 Stereo Audio, Component, 4 X HDMI, USB A for content, USB B for Touch, RS232 Output: Speaker 2 x 3.5 Mono, SPDIF, Line level output			Input: VGA + 3.5 Stereo Audio, Component, 4 X HDMI, USB A for content, USB B for Touch, RS232 Output: Speaker 2 x 3.5 Mono, SPDIF, Line level output	